


# XTRAVAC 640

Vacuum Packaging Machines



## Machine Information XTRAVAC 640

Machine Material	All stainless
Machine Style	Double chamber
Amount of Sealbars	4
Sealbar length inch	25.5"
Sealbar length mm	640 mm
By-Active Sealbars	Optional
Hot wire cut off	Optional
Distance between bars inch	22.5"
Distance between bars mm	570 mm
Vacuum pump (M3/HP)	100/5
Gas flush	Optional
Chamber height inch	8"
Chamber height mm	200 mm
Machine on wheels	Standard
Leverage legs	Standard
Chamber lid movement	Manual
Machine Dim inch	60" X 33" X 40"
Machine Dim mm	1520 X 830 X 1010 mm
Chamber Dim inch	29" X 27" X 8"
Chamber Dim mm	735 X 685 X 200 mm
Machine controls	Digital/Programmable
Machine weight kg	424
Machine weight lbs	930
Electrical connection	220 V 3 ph/60hz, 400 V 3 ph/50hz
Gross weight kg	474
Gross weight lbs	1000
Package Dimension inch	70" x 35.4" x 48.2"
Package Dimension mm	1770 x 900 x 1225 mm

## Model 640

The economical XtraVac 640 features stainless steel construction, long sealbars, balanced lid movement, double-seal system and height adjustable, solid UHMW filler plates. This model also offers a quality Busch pump and storable program controls as standard features.

**XTRAVAC**  
 Vacuum Packaging Machines  
 VC999 Packaging Systems, Kansas City MO  
 Tel. 800-728-2999, Fax 816-472-1999