

XTRAVAC 900A

Vacuum Packaging Machines



Machine Information XTRAVAC 900A

Machine Material	All stainless
Machine Style	Double chamber
Amount of Sealbars	4
Sealbar length inch	34"
Sealbar length mm	860mm
By-Active sealbars	Optional
Hot wire cut off	Optional
Distance between bars inch	40"
Distance between bars mm	1000 mm
Vacuum pump (M3/HP)	302/12.5
Gas Flush	Optional
Chamber height inch	8"
Chamber height mm	200
Machine on wheels	Standard
Leveling legs	Standard
Chamber lid movement	Semi or fully automatic
Machine Dim inch	81" X 53" X 41"
Machine Dim mm	2100 X 1330 X 1050 mm
Chamber Dim inch	41" X 46" X 8"
Chamber Dim mm	1040 X 1150 X 200 mm
Machine controls	Digital/Programmable
Machine weight kg	905
Machine weight lbs	2000
Electrical connection	220 V 3 ph/60hz, 400 V 3 ph/50hz
Compressed air	80 psi at 1 cfm
Gross weight kg	1105
Gross weight lbs	2430
Package Dimension inch	82" x 54" x 50"
Package Dimension mm	2100 x 1370 x 1285 mm

Model 900A

Featuring the longest distance between seal bars automatic lid movement, the economical XtraVac 900A also offers double seam sealing and the height adjustable, solid UHMW filler plates. The unique design of this model allows a single operator to load and unload product from one side of the machine. This model also features, as a standard, storable program controls and a Busch pump.

XTRAVAC
 Vacuum Packaging Machines
 VC999 Packaging Systems, Kansas City, MO
 Tel. 800-728-2999, Fax 816-472-1999