

# XTRAVAC 800L

Vacuum Packaging Machines



## Machine Information XTRAVAC 800L

Machine Material	All stainless
Machine Style	Single chamber
Amount of Sealbars	2
Sealbar length inch	24" (left side), 31.5" (front)
Sealbar length mm	609.60 mm (left side), 800.1 mm (front)
Distance between left bar inch	30.5"
Distance between left bar mm	775 mm
Distance between front bar inch	25.4"
Distance between front bar mm	645 mm
Vacuum pump (M3/HP)	100/5
Chamber height inch	9"
Chamber height mm	230 mm
Machine on wheels	Standard
Leveling legs	Standard
Chamber lid movement	Manual
Machine Dim inch	36" X 31.5" X 42.5"
Machine Dim mm	920 X 800 X 1080 mm
Chamber Dim inch	33" X 27.75" X 9"
Chamber Dim mm	835 X 705 X 230 mm
Machine controls	Digital/Programmable
Machine weight kg	300
Machine weight lbs	660
Hot wire cut off	Optional
Gas flush	Optional
280 MM (11") High lid	Optional
Bi-active sealing	Optional
Electrical connection	220 V 3 ph/60hz, 400 V 3 ph/50hz
Gross weight kg	372
Gross weight lbs	800
Package Dimension inch	38" x 36" x 51"
Package Dimension mm	960 x 920 x 1290 mm

## Model 800L

The XtraVac 800L is a large, single chamber vacuum machine idea for small to medium production. The 800L features a sanitary design and stainless steel construction. Single operator design with Left/Front double sealbar configuration that accommodates high production volume. Height adjustable, solid UHMW filler plates. User-friendly digital controls with storable process control program capabilities. High quality Busch pump and locking casters are standard. The 800L is most often the choice of small to medium sized independent processors, hotels, restaurants, institutions, grocery stores and R&D labs.

**XTRAVAC**  
 Vacuum Packaging Machines  
 VC999 Packaging Systems, Kansas City, MO  
 Tel. 800-728-2999, Fax 816-472-1999