

XTRAVAC TS340

Vacuum Packaging Machines



Machine Information XTRAVAC TS340

Seal only	Yes
Vacuum / Gas	Yes
Skin	No
Max. Tray Dimension 1-up	320 x 250 x 110 mm
Max. Tray Dimension 2-up	146 x 250 x 110 mm
Max. Tray Dimension 3-up	88 x 250 x 110 mm
Max. Tray Dimension 4-up	146 x 111 x 110 mm
Max. Tray Dimension 6-up	88 x 111 x 110 mm
Min. Tray Dimension round	90 mm
Min. Tray height	15 mm
Max Tray height	110 mm
Easy-peel corner	Optional
Shrink film	Optional
Max roll diameter	340 mm
Max Film width	400 mm
Film core mm	75
Vacuum pump size [m3/hp]	40/2.5
Water Cooling	No
Printed Film	Yes
Automatic Die movement	Yes
Cycles per minute Seal only	4-5
Cycles per minute Seal & Gas	2-3
Machine on casters	Yes
Gas pressure [bar]	6
Compressed air [bar]	6
Compressed air	80 psi at 1 cfm
Electrical connection	220 V 3 ph/60hz, 400 V 3 ph/50hz
Machine weight kg	225
Machine weight lbs	490
Gross weight kg	272
Gross weight lbs	590
Package Dimension inch	40" x 31" x 64"
Package Dimension mm	1000 x 790 x 1620 mm
USA	
# 3 Plastic tray dim.	172 mm x 222 mm 1 up
# 5 - SEL Universal tray dim.	207 mm x 262 mm 1 up
# 9 - LEL Family tray dim.	260 mm x 314 mm 1 up
# 10 - LEL Plastic tray dim.	172 mm x 273 mm 1 up
Europe	
187x137mm SEL	2 up
190x144mm SEL	2 up
227x178mm LEL	1 up
230x145mm (XPS tray) SEL	2 up
265x160mm (1/4 Gastronorm) LEL	1 up
SEL Short Edge Leading	
LEL Long Edge Leading	

Model TS340

Large, preformed tray packaging machine features sanitary design and stainless steel construction. Automatic chamber movement design to accommodate high production volume. User-friendly digital controls with storable process control program. Interchangeable tooling for maximum flexibility. Automatic trim wind up. High quality Busch pump standard. Features locking casters.

XTRAVAC
 Vacuum Packaging Machines
 VC999 Packaging Systems, Kansas City, MO
 Tel. 800-728-2999, Fax 816-472-1999